





HSF RoHS

SPECIFICATIONS

Current rating: 5.6AMP.
 Contact resistance: 15mΩ max. at 100mA DC
 Insulation resistance: 1000MΩ min. at 500V DC
 Dielectric withstanding voltage: 1500V AC For 1minute
 Operating temperature: -55°C TO +125°C

Contact Material: Copper Alloy
 Contact Plating: Au or Sn Over Ni
 Insulator Material: Polyester(UL94V-0)
 Standard: PBT
 Max.Processing Temp: 245°C±5°C For 5 Second



Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)

Ordering Information


35133 48 A F S XX B N A X

No.of Pins
48PIN

Contact Type
F=Female

Contact Plating
G0:Gold Flash
S0:Gold Flash/Tin
S1:3U" Gold/Tin
S2:5U" Gold/Tin
S3:10U" Gold/Tin
S4:15U" Gold/Tin
S5:30U" Gold/Tin
SN:Tin

Stream Code



					OPERATION	DRAW	Jelly Feng	2023.03.29	SCALE	FIT
					X.X ±0.30	CHECK			UNIT	mm
					X.XX ±0.20				SIZE	A4
					X.XXX ±0.10				SHEET	1/1
A0	2023.03.29	NEW DRAWING			Angle ±3°	APPROVE			PROJ.	
REV	DATE	MODIFICATION DESCRIPTION			DIM TOL					

JILN 深圳市锦凌电子有限公司
 SHENZHEN JINLING ELECTRONICS CO.,LTD
 Tel : 86-755-27483253 Fax: 86-755-2997-5588

PART NO. 351348AFSXXBNAX
 TITLE: DIN 41612 of 5.08mm pitch large current F-type high plastic

A

A